

PRODUCT INFORMATION



VALVOLINE™ EXTREME EP2 GREASE

Valvoline™ Extreme EP2 Grease is a premium quality lithium soap grease containing an extreme pressure additive, formulated to provide outstanding mechanical stability & EP characteristics under severe operating conditions. It is a multi-purpose grease developed for use in a variety of operating conditions.

Valvoline™ Extreme EP2 Grease is recommended for lubrication of both plain & anti-friction bearings in a wide variety of applications such as automotive, earth-moving equipment, gear coupling, mining equipment & other industrial applications.

EXTREME EP2 GREASE ADVANTAGES

- Provides excellent lubrication in both high and low temperature conditions.
- The product combines oxidation, anti-wear and corrosion inhibitors with high quality base stocks.
- It provides good resistance to water wash-out and perform well under heavy load and high speed conditions.
- It maintains excellent pumpability at low temperatures with a drop point of 180°C.
- The product is suitable for use where working temperature is up to 130°C.

PERFORMANCE LEVEL

IS 7623 : 1993 (EP Type)

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
NLGI Grade	2
Type of Soap	Lithium
Texture	Buttery
Worked Penetration (60 Strokes) @ 25°C	278
Drop Point, °C, min	180
Rust Tests	Pass
Four ball wear scar dia, mm., max	0.6
Four ball wear load, Kg., min	200
Timken OK Load, Kg., min	20

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Effective Date

Oct 2020

Author

AUS