

# PRODUCT INFORMATION



## VALVOLINE ATF + 4™ TRANSMISSION FLUID

**Valvoline ATF + 4** is a uniquely blended automatic transmission fluid that meets Chrysler Material Standard MS-9602. It is designed as a factory fill fluid for all 1998 and later Chrysler Corporation automatic transmissions and transaxles. It is fully compatible with all transmissions that require Mopar ATF +®, Mopar ATF+2™ and Mopar ATF+3™. Valvoline ATF + 4 is for use in all applications specifying Mopar ATF+4 or Type MS-9602 fluid.

### ATF + 4™ TRANSMISSION FLUID ADVANTAGES

- Improved thermal stability for longer fluid life.
- Improved viscosity stability for consistent transmission operation.
- Specific frictional properties for smooth clutch engagement.
- Contains special additives to prevent rust corrosion and wear for longer life.
- Contains additive to reduce foaming.

### PERFORMANCE LEVEL

Mopar ATF+ MS 7176®

Mopar ATF+2® MS 7176

Mopar ATF+3™

Mopar ATF+4™

### Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	ATF+4
Viscosity @ 100C, cSt	7.55
Viscosity @ 40C, cSt	34.13
Viscosity Index	198
Specific Gravity @ 15 C	0.8506
Density, kg/L	0.8387
Pour Point, C, max.	-48
Brookfield Viscosity @ -40C, cP	9,000
Flash Point, COC, C	196

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Effective Date

Oct 2020

Author

NW